

81/82

端接式电磁屏蔽防水接头 EMV End type Cable Gland



主体材质：黄铜镀镍

Material: Nickel-plated brass

温度：-40℃~+100℃，短时间 120℃

Temperature range: -40℃~ +100℃, short-term to 120℃

防护等级：IP68(使用 O 型圈的情况下)

Protection Degree: IP68(Using O-sealing)

特性：可屏蔽电磁干扰，不含卤素和镉，同时具有极好的抗冲击强度。

Properties: Resistant to EMI shielding free of halogen, and cadmium, with excellent impact strength.



型号 Part no.	螺纹 A Thread	B	尺寸 Dimension(mm)			包装(个) Packing
			C	E	F	
HSM-M25-AJ(10-16)/EMV-AD-7	M25X1.5	7.0	3.2	14.8	27.0	25
HSM-M25-AJ(10-16)/EMV-AD-12	M25X1.5	12.0	3.2	14.8	27.0	25
HSM-M25-AJ(13-18)/EMV-AD-7	M25X1.5	7.0	3.2	14.8	30.0	25
HSM-M25-AJ(13-18)/EMV-AD-12	M25X1.5	12.0	3.2	14.8	30.0	25
HSM-M32-AJ(15-22)/EMV-AD-8	M32X1.5	8.0	4.0	21.8	35.0	20
HSM-M32-AJ(15-22)/EMV-AD-13	M32X1.5	13.0	4.0	21.8	35.0	20
HSM-M32-AJ(18-25)/EMV-AD-8	M32X1.5	8.0	4.0	21.8	40.0	20
HSM-M32-AJ(18-25)/EMV-AD-13	M32X1.5	13.0	4.0	21.8	40.0	20
HSM-M40-AJ(18-25)/EMV-AD-8	M40X1.5	8.0	4.5	29.8	45.0	20
HSM-M40-AJ(18-25)/EMV-AD-13	M40X1.5	13.0	4.5	29.8	45.0	20
HSM-M40-AJ(22-32)/EMV-AD-8	M40X1.5	8.0	4.5	29.8	50.0	20
HSM-M40-AJ(22-32)/EMV-AD-13	M40X1.5	13.0	4.5	29.8	50.0	20
HSM-M50-AJ(32-28)/EMV-AD-9	M50X1.5	9.0	5.0	39.8	57.0	10
HSM-M50-AJ(32-38)/EMV-AD-14	M50X1.5	14.0	5.0	39.8	57.0	10