

EMC Straight fitting with swivel



Material: Polyamide 66, Nickel plated brass thread

Colour: Black(BL) /Grey(GR)

Temperature range: -45°C ~ +120°C , short-term to 150°C

Protection Degree: IP66, IP68(For use with conduits & RLS seal)

Properties: High shielding alternation and low coupling resistance. Disturbance signals such as electrical signals and magnetic fields will be discharged to the housing/casing. Easy and quick installation. Fasten the cable. Suitable for occasional rotation.



CE  ULtest EN45545

METRIC THREAD

Fits to Conduit size	Part no.	A Thread	B	C	D	E	F	G	Packing (pcs)
28	RL28-M25-CS90-X/EMV-11	M25X1.5	12.0	71.5	36.5	14.8	36.0	80.5	50
28	RL28-M25-CS90-X/EMV-7	M25X1.5	7.0	66.5	36.5	14.8	36.0	80.5	50
34	RL34-M32-CS90-X/EMV-12	M32X1.5	13.0	89.0	43.0	21.8	42.0	100.5	20
34	RL34-M32-CS90-X/EMV-8	M32X1.5	8.0	84.0	43.0	21.8	42.0	100.5	20
42	RL42-M40-CS90-X/EMV-13	M40X1.5	13.0	100.5	53.0	29.8	50.0	119.5	20
42	RL42-M40-CS90-X/EMV-8	M40X1.5	8.0	95.5	53.0	29.8	50.0	119.5	20
54	RL54-M50-CS90-X/EMV-14	M50X1.5	14.0	114.5	66.0	39.8	60.0	133.5	10
54	RL54-M50-CS90-X/EMV-9	M50X1.5	9.0	109.5	66.0	39.8	60.0	133.5	10