

## RL/X Straight fitting, swivel, with metal external thread



Material: Polyamide 66, Nickel plated brass thread

Colour: Black(BL) /Grey(GR)

Temperature range: -45°C ~ +120°C , short-term to 150°C

Protection Degree: IP66, IP68(For use with conduits & RLS seal)

Properties: Free of halogen and cadmium, very high impact resistance, high thread and system connection strength, suitable for occasional rotation.



CE  ULtest EN45545

### M THREAD

Fits to Conduit size	Part no.	A Thread	B	C	D	E	F	Packing (pcs)
16	RL16-M16-SA/X	M16X1.5	11.5	58.9	22.0	11.6	24.0	50
16	RL16-M20-SA/X	M20X1.5	14.0	61.4	22.0	11.6	24.0	50
21	RL21-M20-SA/X	M20X1.5	14.0	64.0	28.0	15.0	28.0	50
21	RL21-M25-SA/X	M25X1.5	16.0	67.0	28.0	15.0	30.0	50
28	RL28-M25-SA/X	M25X1.5	16.0	67.1	36.4	20.3	36.0	50
28	RL28-M32-SA/X	M32X1.5	16.0	67.1	36.4	20.3	40.0	50
34	RL34-M32-SA/X	M32X1.5	16.0	70.0	43.0	26.5	42.0	30
34	RL34-M40-SA/X	M40X1.5	16.0	70.0	43.0	26.5	50.0	30
42	RL42-M40-SA/X	M40X1.5	16.0	75.8	52.5	31.3	50.0	30
42	RL42-M50-SA/X	M50X1.5	16.0	75.8	52.5	31.3	60.0	30
54	RL54-M50-SA/X	M50X1.5	16.0	81.2	66.0	40.5	60.0	10
54	RL54-M63-SA/X	M63X1.5	16.0	81.2	66.0	40.5	70.0	10

### PG THREAD

Fits to Conduit size	Part no.	A Thread	B	C	D	E	F	Packing (pcs)
13	RL13-PG9-SA/X	PG9	12.0	53.2	19.5	11.6	24.0	50
16	RL16-PG11-SA/X	PG11	12.0	59.4	22.0	11.6	24.0	50
21	RL21-PG13-SA/X	PG13	13.0	64.0	28.0	15.0	28.0	50
21	RL21-PG16-SA/X	PG16	13.0	64.0	28.0	15.0	28.0	50
28	RL28-PG21-SA/X	PG21	14.0	65.1	36.4	20.3	36.0	50
34	RL34-PG29-SA/X	PG29	14.0	68.0	43.0	26.5	42.0	30
42	RL42-PG36-SA/X	PG36	17.0	76.8	52.5	31.3	52.0	30
54	RL54-PG48-SA/X	PG48	17.0	82.2	66.0	40.5	70.0	10