

RL/X 90° Elbow fitting, swivel, with metal internal thread



Material: Polyamide 66, anodized aluminium thread

Colour: Black(BL) /Grey(GR)

Temperature range: -45°C ~ +120°C , short-term to 150°C

Protection Degree: IP66, IP68(For use with conduits & RLS seal)

Properties: Free of halogen and cadmium, very high impact resistance, high thread and system connection strength, suitable for occasional rotation.

CE ULtest EN45545

UNEF THREAD

Fits to Conduit size	Part no.	A Thread	B	C	D	E	F	G	Packing (pcs)
13	RL13-U063-CSF90/X	5/8"-24UNEF	9.0	44.7	19.5	11.5	22.0	63.0	50
16	RL16-U063-CSF90/X	5/8"-24UNEF	9.0	46.8	22.0	11.6	23.0	65.3	50
16	RL16-U075-CSF90/X	3/4"-20UNEF	9.5	52.3	22.0	11.6	23.0	65.3	50
21	RL21-U075-CSF90/X	3/4"-20UNEF	9.5	52.3	28.0	15.0	28.0	70.0	50
21	RL21-U081-CSF90/X	13/16"-20UNEF	9.5	60.5	28.0	15.0	28.0	70.0	50
28	RL28-U094-CSF90/X	15/16"-20UNEF	9.5	60.5	36.5	20.3	35.0	80.0	20
28	RL28-U100-CSF90/X	1"-20UNEF	9.5	60.5	36.5	20.3	35.0	80.0	20
34	RL34-U113-CSF90/X	1 1/8"-18UNEF	9.5	77.5	43.0	26.5	41.0	100.0	20
34	RL34-U119-CSF90/X	1 3/16"-18UNEF	9.5	77.5	43.0	26.5	41.0	100.0	20
34	RL34-U125-CSF90/X	1 1/4"-18UNEF	9.5	77.5	43.0	26.5	41.0	100.0	20
34	RL34-U131-CSF90/X	1 5/16"-18UNEF	9.5	77.5	43.0	26.5	41.0	100.0	20
34	RL34-U138-CSF90/X	1 3/8"-18UNEF	9.0	77.0	43.0	26.5	41.0	100.0	20
42	RL42-U144-CSF90/X	1 7/16"-18UNEF	9.5	88.8	53.0	31.3	48.0	118.0	10
42	RL42-U175-CSF90/X	3/4"-18UNEF	11.5	90.8	53.0	31.3	48.0	118.0	10
54	RL54-U200-CSF90/X	2"-18UNEF	12.0	104.5	66.0	40.5	60.0	133.0	5