

Y Fitting

Material: Polyamide 66

Colour: Black(BL)

Temperature range: -45°C ~ +120°C , short-term to 150°C

Protection Degree: IP66, IP68(For use with conduits & RLS seal)

Properties: Free of halogen and cadmium, very high impact resistance, high conduit pull out strength.

CE  **ULtest EN45545**
China Railway No.67 test



Fits to Conduit size	Part no.	Special no.	A	B	C	D	E	F	G	Packing (pcs)
13X10X10	RL131010/Y	YPA66-10-2x7	21.0	69.3	28.2	5.0	32.7	21.2	14.6	10
16X13X13	RL161313/Y	YPA66-12-2x10	25.0	74.0	42.0	5.5	31.0	22.3	19.1	10
21X16X16	RL211616/Y	YPA66-17-2x12	32.0	85.0	51.0	6.5	32.0	28.0	28.7	10
28X21X21	RL282121/Y	YPA66-23-2x17	38.0	90.5	63.8	6.5	38.0	36.4	35.8	10
34X28X28	RL342828/Y	YPA66-29-2x23	45.0	106.0	76.8	6.5	37.0	43.0	40.4	10
42X34X34	RL423434/Y	YPA66-36-2x29	53.5	125.7	95.9	6.5	48.3	52.5	53.0	10
54X42X42	RL544242/Y	-	64.0	129.0	109.4	6.5	53.0	66.5	57.0	10

Note: Special no. is for China railway passenger cars, other passenger vehicles, motor trains unit and special vehicle exclusive models