

39/40

Hinged "Y" piece

Material: Polyamide 66

Colour: Black(BL)

Temperature range: -45°C ~ +120°C , short-term to 150°C

Protection Degree: IP40

Properties : Free of halogen and cadmium, very high impact resistance, high conduit pull out strength.



Part no.	A Thread	B	C	D	E	Packing (pcs)
Y101010/BL	54.6	37.1	10	10	10	10
Y101013/BL	54.6	37.1	10	10	10	10
Y101210/BL	54.6	37.1	10	10	10	10
Y131010/BL	54.6	37.1	10	10	10	10
Y131310/BL	54.6	37.1	10	10	10	10
Y131313/BL	54.6	37.1	10	10	10	10
Y161013/BL	54.9	39.8	10	10	10	10
Y161310/BL	54.9	39.8	10	10	10	10
Y161313/BL	54.9	39.8	10	10	10	10
Y161610/BL	54.9	39.8	10	10	10	10
Y161613/BL	54.9	39.8	10	10	10	10
Y211010/BL	42.8	41.0	12	10	10	10
Y211310/BL	42.8	41.0	12	10	10	10
Y211313/BL	42.8	41.0	12	10	10	10
Y211610/BL	48.2	39.8	12	10	10	10
Y211613/BL	48.2	39.6	12	10	10	10
Y211616/BL	63.6	47.5	12	10	10	10
Y212110/BL	57.9	44.9	12	12	10	10
Y212113/BL	57.9	44.9	12	12	10	10
Y212116/BL	63.6	47.5	12	12	10	10
Y282113/BL	54.0	48.8	13	12	10	10
Y282116/BL	54.0	48.8	13	12	10	10
Y282121/BL	76.5	60.0	13	11	11	10
Y282810/BL	67.3	55.9	13	13	10	10
Y282813/BL	67.3	55.9	13	13	10	10
Y282816/BL	67.3	55.9	13	13	10	10
Y282821/BL	76.5	60.0	13	13	12	10
Y282828/BL	90.7	67.0	13	13	13	10
Y343416/BL	100.6	75.0	13	13	13	10
Y343421/BL	100.6	76.0	13	13	13	10
Y343434/BL	100.6	82.1	13	13	13	10