

Brass external thread Straight fitting

Material: Nickel-plated brass

Temperature range: -40°C ~ +125°C

Protection Degree: IP40-68

Fitting conduits: SC, SPC, SPLC,SBC,SSC,SPUL,RPC,SSPC



METRIC THREAD

Fits to conduit size	Part no.	A Thread	B	C	D	E	Packing (pcs)
5/16"	SPC12-M16-M	M16X1.5	8.5	20.0	22.0	12.0	50
3/8"	SPC16-M16-M	M16X1.5	8.5	21.0	26.0	13.0	50
3/8"	SPC16-M20-M	M20X1.5	8.5	21.0	26.0	13.0	50
1/2"	SPC20-M20-M	M20X1.5	9.0	25.0	28.0	13.0	50
3/4"	SPC25-M25-M	M25X1.5	12.0	25.5	35.0	14.5	50
1"	SPC32-M32-M	M32X1.5	14.0	28.5	45.0	17.0	50
1 1/4"	SPC40-M40-M	M40X1.5	14.0	30.5	55.0	17.0	25
1 1/2"	SPC45-M50-M	M50X1.5	-	-	-	-	20

PG THREAD

Fits to conduit size	Part no.	A Thread	B	C	D	E	Packing (pcs)
5/16"	SPC12-PG9-M	PG9	-	-	-	-	50
3/8"	SPC16-PG11-M	PG11	8.5	21.0	26.0	13.0	50
3/8"	SPC16-PG13.5-M	PG13.5	9.0	21.0	26.0	13.0	50
1/2"	SPC20-PG16-M	PG16	8.0	23.0	28.0	13.0	50
3/4"	SPC25-PG21-M	PG21	12.0	25.5	35.0	14.5	50
1"	SPC32-PG29-M	PG29	14.0	30.5	45.0	16.0	50
1 1/4"	SPC40-PG36-M	PG36	16.0	39.0	59.0	19.0	25
1 1/2"	SPC45-PG48-M	PG48	-	-	-	-	20