

# 75/76

## Metal Cable Gland with Multi-core

Body Material: Nickel-plated brass

Sealing Material: Nylon 66 and NBR

Temperature range: -40°C ~ +100°C , short-term to 120°C

Protection Degree: IP65



### METRIC THREAD

Thread	Part no.	Clamping range	GL	Dimension(mm) AG	SW	Packing (pcs)
M16X1.5	HSM-M16(2X3)	2XØ3	6.0	16.0	17.0	50
M20X1.5	HSM-M20(6X3)	6XØ3	7.0	20.0	22.0	50
M20X1.5	HSM-M20(2X5)	2XØ5	7.0	20.0	22.0	50
M25X1.5	HSM-M25(2X7)	2XØ7	8.0	25.0	30.0	25
M25X1.5	HSM-M25(4X6)	4XØ6	7.0	25.0	30.0	25
M25X1.5	HSM-M25(3X7)	3XØ7	7.0	25.0	30.0	25
M25X1.5	HSM-M25(2X8)	2XØ8	7.0	25.0	30.0	25
M32X1.5	HSM-M32(4X9)	4XØ9	8.0	32.0	40.0	25
M40X1.5	HSM-M40(5X9)	5XØ9	9.0	40.0	50.0	20
M40X1.5	HSM-M40(2X15)	2XØ15	9.0	40.0	50.0	20

### PG THREAD

Thread	Part no.	Clamping range	GL	Dimension(mm) AG	SW	Packing (pcs)
PG9	HSM-PG9(2X3)	2XØ3	6.0	15.2	17.0	50
PG21	HSM-PG21(4X6)	4XØ6	7.0	28.3	30.0	50
PG21	HSM-PG21(3X7)	3XØ7	7.0	28.3	30.0	50
PG21	HSM-PG21(2X6)	2XØ6	9.0	28.3	30.0	50
PG21	HSM-PG21(2X7)	2XØ7	8.0	28.3	30.0	50
PG21	HSM-PG21(2X8)	2XØ8	7.0	28.3	30.0	25
PG29	HSM-PG29(4X9)	4XØ9	8.0	37.0	40.0	20
PG36	HSM-PG36(5X9)	5XØ9	9.0	47.0	50.0	10