## RL 45°Elbow fitting-fixed external thread

Material: Polyamide 66 Colour: Black(BL) /Grey(GR)

Temperature range: -45°C ~ +120°C , short-term to 150°C Protection Degree: IP66, IP68(For use with conduits & RLS seal)

Properties: Self-extinguishing, free of halogen, phosphor and cadmium, with

excellent impact strength.

## **C** € **③** ULtest EN45545



## **METRIC THREAD**

Fits to Conduit size	Part no.	A Thread	В	С	D	E	F	G	Packing (pcs)
13	RL13-M16-45	M16X1.5	11.5	41.2	20.0	11.4	22.0	37.6	50
16	RL16-M16-45	M16X1.5	11.5	43.5	22.0	11.6	22.0	40.9	50
21	RL21-M20-45	M20X1.5	13.0	50.2	28.5	15.0	27.0	44.7	50
28	RL28-M25-45	M25X1.5	16.0	61.4	37.0	20.3	36.0	53.9	50
34	RL34-M32-45	M32X1.5	16.0	64.7	43.5	26.5	42.0	58.9	20
42	RL42-M40-45	M40X1.5	16.0	85.7	53.0	31.3	53.0	75.2	20
54	RL54-M50-45	M50X1.5	16.0	102.9	66.0	40.5	67.0	90.0	10
54	RL54-M63-45	M63X1.5	16.0	106.0	66.0	47.0	73.0	90.0	10

## **PG THREAD**

Fits to Conduit size	Part no.	A Thread	В	С	D	E	F	G	Packing (pcs)
13	RL13-PG9-45	PG9	11.0	41.2	20.0	11.4	22.0	37.6	50
16	RL16-PG11-45	PG11	11.0	45.0	22.0	12.5	25.0	40.9	50
21	RL21-PG13-45	PG13	11.5	50.7	23.0	15.5	28.0	44.7	50
21	RL21-PG16-45	PG16	11.5	51.7	28.5	17.7	30.0	44.7	50
28	RL28-PG21-45	PG21	12.0	61.3	37.0	21.5	36.0	53.9	50
34	RL34-PG29-45	PG29	12.0	66.2	43.5	28.0	45.0	58.8	20
42	RL42-PG36-45	PG36	12.0	88.7	53.0	38.0	59.0	75.2	20
54	RL54-PG48-45	PG48	15.0	101.9	66.0	50.0	69.0	90.0	10