

Nylon cable gland with multi-core

Body Material: Nylon 66

Sealing Material: NBR

Colour: Black(BL)/Grey(GR)

Temperature range: -40°C ~ +100°C , short-term to 120°C

Protection Degree: IP68(Using O-sealing)



METRIC THREAD

Thread	Part no.	Clamping range	GL	Dimension(mm) AG	SW	Packing (pcs)
M16X1.5	HSK-M16(2X3)	2XØ3	6.0	16.0	17.0	50
M20X1.5	HSK-M20(6X3)	6XØ3	7.0	20.0	22.0	50
M20X1.5	HSK-M20(2X5)	2XØ5	7.0	20.0	22.0	50
M25X1.5	HSK-M25(2X7)	2XØ7	8.0	25.0	30.0	25
M25X1.5	HSK-M25(4X6)	4XØ6	7.0	25.0	30.0	25
M25X1.5	HSK-M25(3X7)	3XØ7	7.0	25.0	30.0	25
M25X1.5	HSK-M25(2X8)	2XØ8	7.0	25.0	30.0	25
M32X1.5	HSK-M32(4X9)	4XØ9	8.0	32.0	40.0	25
M40X1.5	HSK-M40(5X9)	5XØ9	9.0	40.0	50.0	20
M40X1.5	HSK-M40(2X15)	2XØ15	9.0	40.0	50.0	20

PG THREAD

Thread	Part no.	Clamping range	GL	Dimension(mm) AG	SW	Packing (pcs)
PG9	HSK-PG9(2X3)	2XØ3	6.0	15.2	17.0	50
PG21	HSK-PG21(4X6)	4XØ6	7.0	28.3	30.0	50
PG21	HSK-PG21(3X7)	3XØ7	7.0	28.3	30.0	50
PG21	HSK-PG21(2X6)	2XØ6	9.0	28.3	30.0	50
PG21	HSK-PG21(2X7)	2XØ7	8.0	28.3	30.0	50
PG21	HSK-PG21(2X8)	2XØ8	7.0	28.3	30.0	25
PG29	HSK-PG29(4X9)	4XØ9	8.0	37.0	40.0	20
PG36	HSK-PG36(5X9)	5XØ9	9.0	47.0	50.0	10