

高温穿线管 Fire-resisting sleeves

材质：内层碱玻璃纤维，外层硅树脂

Material: Inner alkali glass fiber, other silicone

颜色：红色

Colour: Red

特性：防火，耐高温，防海水，防酸性，防油脂，耐摩擦，柔韧性好，阻燃自行熄灭

Properties: Fire protection, high temperature resistance, widely resistant to seawater, acids and oils, abrasive resistant, very flexible, non-flammable even no afterglow, self-extinguishing.

应用：钢铁行业，铸造技术，化工厂，石油平台，造船业，公交行业，采矿业，玻璃生产

Applications: Steel industry, Foundries, Chemical companies, Oil companies, Shipbuilders, Public transportation, Mining industry, Glass factories.



| 型号 Part no. | 标称内径 (mm) Insid diameter | 涂层厚 (mm) Coating thickness | 工作温度 Operating TEMP | 瞬间耐温 Max short term TEMP | 击穿电压 Breakdown voltage | 包装 (米 / 卷) Packing |
|----------------|-----------------------------|-------------------------------|------------------------|-----------------------------|---------------------------|-----------------------|
| HTFR-06 | 6.0 | ≥1.0 | | | | 30 |
| HTFR-08 | 8.0 | ≥1.0 | | | | 30 |
| HTFR-10 | 10.0 | ≥1.0 | | | | 30 |
| HTFR-12 | 12.0 | ≥1.0 | | | | 30 |
| HTFR-14 | 14.0 | ≥1.0 | | | | 30 |
| HTFR-16 | 16.0 | ≥1.0 | | | | 30 |
| HTFR-19 | 19.0 | ≥1.0 | | | | 30 |
| HTFR-22 | 22.0 | ≥1.0 | | | | 30 |
| HTFR-25 | 25.0 | ≥1.0 | | | | 30 |
| HTFR-29 | 29.0 | ≥1.0 | | | | 30 |
| HTFR-32 | 32.0 | ≥1.2 | | | | 20 |
| HTFR-35 | 35.0 | ≥1.2 | | | | 20 |
| HTFR-38 | 38.0 | ≥1.2 | ≥260°C | ≥1300°C | ≥10-15KV | 20 |
| HTFR-41 | 41.0 | ≥1.2 | | | | 20 |
| HTFR-44 | 44.0 | ≥1.2 | | | | 20 |
| HTFR-51 | 51.0 | ≥1.2 | | | | 15 |
| HTFR-57 | 57.0 | ≥1.2 | | | | 15 |
| HTFR-64 | 64.0 | ≥1.2 | | | | 15 |
| HTFR-70 | 70.0 | ≥1.2 | | | | 15 |
| HTFR-76 | 76.0 | ≥1.5 | | | | 15 |
| HTFR-83 | 83.0 | ≥1.5 | | | | 15 |
| HTFR-89 | 89.0 | ≥1.5 | | | | 15 |
| HTFR-95 | 95.0 | ≥1.5 | | | | 15 |
| HTFR-100 | 100.0 | ≥1.5 | | | | 15 |