

## 阻燃缠绕管

### Flame retardant spiral wrap

材质：聚乙烯

Material: Polyethylene

颜色：黑色 / 白色

Colour: Black/White

温度：-30°C~+100°C

Temperature range: -30°C~+100°C

阻燃等级：UL94-V0

Flame- retardant: UL94-V0

特性：可以用于包装电线和线束，使之整齐美观。同时能保护电线不受损害。使用时先将一端固定然后按顺时针方向将管子缠绕在电线上，最后扎紧即可。

Properties: spiral wrap is an economical way for cable management. It can be easily applied to wire harness, cables and wire bundles keep all your wires tidy and beautiful. Simply fix one end by hand first, then wrapped around the cable in a clockwise direction and tighten it up. silver, bright color.



型号 Part no.	外径 O(mm) Fitted	带宽 W(mm) Pitch	壁厚 (mm) Wall thickness	包装 (米 / 卷) Packing
MCRG-04	4.7	6.0~6.5	0.6±0.1	100
MCRG-06	6.0	7.0~7.5	0.7±0.1	80
MCRG-08	8.0	8.8~9.5	0.8±0.1	60
MCRG-10	10.0	10.0~10.8	1.0±0.1	40
MCRG-12	12.0	12.0~12.8	1.2±0.1	30
MCRG-14	14.0	14.0~15.0	1.3±0.1	20
MCRG-16	16.0	15.5~16.5	1.5±0.1	18
MCRG-18	18.0	16.5~17.5	1.6±0.1	15
MCRG-20	20.0	19.0~20.0	1.7±0.1	14
MCRG-22	22.0	19.0~20.0	1.75±0.1	12
MCRG-25	25.0	23.0~24.0	1.85±0.1	10
MCRG-30	30.0	28.0~30.0	2.4±0.1	6
MCRG-35	35.0	32.0~34.0	2.5±0.1	5
MCRG-40	40.0	33.0~35.0	2.7±0.1	4
MCRG-50	50.0	44.0~46.0	2.8±0.1	2.5