

# 尼龙闷盖

## Nylon Plug

材质：尼龙 66

Material: Polyamide 66

颜色：黑色 / 灰色

Colour: Black(BL) /Grey(GR)

温度：-40°C~+120°C，短时间 150°C

Temperature range: -40°C~+120°C, short-term to 150°C

防护等级：IP68(使用 O 型圈的情况下)

Protection Degree: IP68(Using O-sealing)



### M 螺纹



螺纹 Thread	黑色型号 Part no.(BL)	灰色型号 Part no.(GR)	AG	GL	D	包装(个) Packing
M12X1.5	NLMG-M12X1.5B	NLMG-M12X1.5G	15.0	16.0	7.0	100
M16X1.5	NLMG-M16X1.5B	NLMG-M16X1.5G	16.0	20.0	7.0	100
M18X1.5	NLMG-M18X1.5B	NLMG-M18X1.5G	18.0	23.0	8.0	100
M20X1.5	NLMG-M20X1.5B	NLMG-M20X1.5G	20.0	25.0	9.0	100
M22X1.5	NLMG-M22X1.5B	NLMG-M22X1.5G	22.0	27.0	10.0	100
M24X1.5	NLMG-M24X1.5B	NLMG-M24X1.5G	24.0	29.0	10.0	50
M25X1.5	NLMG-M25X1.5B	NLMG-M25X1.5G	25.0	30.0	11.0	50
M27X2.0	NLMG-M27X2.0B	NLMG-M27X2.0G	27.0	33.0	11.0	50
M30X2.0	NLMG-M30X2.0B	NLMG-M30X2.0G	30.0	35.0	11.0	50
M32X1.5	NLMG-M32X1.5B	NLMG-M32X1.5G	32.0	39.0	11.0	25
M36X2.0	NLMG-M36X2.0B	NLMG-M36X2.0G	36.0	44.0	11.0	25
M40X1.5	NLMG-M40X1.5B	NLMG-M40X1.5G	40.0	46.0	13.0	10
M48X2.0	NLMG-M48X2.0B	NLMG-M48X2.0G	48.0	55.0	13.0	10
M50X1.5	NLMG-M50X1.5B	NLMG-M50X1.5G	50.0	57.0	15.0	10
M63X1.5	NLMG-M63X1.5B	NLMG-M63X1.5G	63.0	70.0	15.0	10

### PG 螺纹

螺纹 Thread	黑色型号 Part no.(BL)	灰色型号 Part no.(GR)	AG	GL	D	包装(个) Packing
PG7	NLMG-PG7B	NLMG-PG7G	12.5	16.0	8.0	100
PG9	NLMG-PG9B	NLMG-PG9G	15.2	19.0	8.0	100
PG11	NLMG-PG11B	NLMG-PG11G	18.6	23.0	8.0	100
PG13.5	NLMG-PG13.5B	NLMG-PG13.5G	20.4	25.0	9.0	100
PG16	NLMG-PG16B	NLMG-PG16G	22.5	27.0	10.0	50
PG21	NLMG-PG21B	NLMG-PG21G	28.3	33.0	11.0	50
PG29	NLMG-PG29B	NLMG-PG29G	37.0	44.0	11.0	25
PG36	NLMG-PG36B	NLMG-PG36G	47.0	55.0	13.0	10
PG42	NLMG-PG42B	NLMG-PG42G	54.0	62.0	15.0	10
PG48	NLMG-PG48B	NLMG-PG48G	59.3	69.0	15.0	5