

15/16

RL 金属外螺纹 45 度弯接头

RL 45° Elbow fitting with metal external thread

材质：尼龙 66，黄铜镀镍螺纹

Material: Polyamide 66, Nickel plated brass thread

颜色：黑色 / 灰色

Colour: Black(BL) / Grey(GR)

温度：-45°C~+120°C，短时间 150°C

Temperature range: -45°C ~ +120°C, short-term to 150°C

防护等级：IP66, IP68(与软管及 RLS 密封垫配合使用)

Protection Degree: IP66, IP68(For use with conduits & RLS seal)

特性：自熄灭性好，不含卤素，磷，镉，同时具有极好的抗冲击强度

Properties: Self-extinguishing, free of halogen, phosphor and cadmium, with excellent impact strength.



CE  UL测试 EN45545

M 螺纹

适配软管尺寸 Fits to Conduit size	型号 Part no.	螺纹 A Thread	B	C	D	E	F	G	包装(个) Packing
13	RL13-M16-S45	M16X1.5	11.5	41.2	20.0	10.7	22.0	40.9	50
16	RL16-M16-S45	M16X1.5	11.5	43.5	22.0	10.7	22.0	43.9	50
21	RL21-M20-S45	M20X1.5	14.0	50.2	28.5	14.5	27.0	47.7	50
28	RL28-M25-S45	M25X1.5	16.0	61.4	37.0	19.0	36.0	56.4	50
34	RL34-M32-S45	M32X1.5	16.0	65.0	43.5	25.5	43.0	56.3	20
42	RL42-M40-S45	M40X1.5	16.0	85.7	53.0	31.7	53.0	76.2	20
54	RL54-M50-S45	M50X1.5	16.0	102.9	66.0	41.2	67.0	90.0	10
54	RL54-M63-S45	M63X1.5	16.0	106.0	66.0	47.0	73.0	90.0	10

PG 螺纹

适配软管尺寸 Fits to Conduit size	型号 Part no.	螺纹 A Thread	B	C	D	E	F	G	包装(个) Packing
13	RL13-PG9-S45	PG9	12.0	41.2	20.0	10.5	22.0	40.9	50
16	RL16-PG11-S45	PG11	12.0	45.0	22.0	12.5	25.0	43.9	50
21	RL21-PG13-S45	PG13	13.0	50.7	23.0	14.5	28.0	47.7	50
21	RL21-PG16-S45	PG16	13.0	51.7	28.5	17.5	30.0	47.7	50
28	RL28-PG21-S45	PG21	14.0	62.4	37.0	22.0	38.0	56.4	50
34	RL34-PG29-S45	PG29	14.0	66.2	43.5	39.0	45.0	56.3	20
42	RL42-PG36-S45	PG36	17.0	88.7	53.0	38.0	59.0	76.2	20
54	RL54-PG48-S45	PG48	17.0	101.9	66.0	49.0	69.0	90.0	10