

RL 金属内螺纹 90 度弯接头

RL 90° Elbow fitting with metal internal thread

材质：尼龙 66，黄铜镀镍螺纹

Material: Polyamide 66, Nickel plated brass thread

颜色：黑色 / 灰色

Colour: Black(BL) / Grey(GR)

温度：-45°C~+120°C，短时间 150°C

Temperature range: -45°C ~ +120°C, short-term to 150°C

防护等级：IP66, IP68(与软管及 RLS 密封垫配合使用)

Protection Degree: IP66, IP68(For use with conduits & RLS seal)

特性：自熄灭性好，不含卤素，磷，镉，同时具有极好的抗冲击强度

Properties: Self-extinguishing, free of halogen, phosphor and cadmium, with excellent impact strength.



CE  **UL测试 EN45545**

已通过铁道客车 67 号文件测试

M 螺纹

适配软管尺寸 Fits to Conduit size	型号 Part no.	铁路专属型号① Special no.	螺纹 A Thread	B	C	D	E	F	G	包装(个) Packing
13	RL13-M16-CSF90	LPA66-10-1/4-CSF90	M16X1.5	14.0	43.1	20.0	10.7	24.0	60.8	50
16	RL16-M16-CSF90	LPA66-12-3/8-CSF90	M16X1.5	14.0	43.9	22.0	11.0	27.0	64.0	50
21	RL21-M20-CSF90	LPA66-17-1/2-CSF90	M20X1.5	15.0	49.1	28.5	15.0	32.0	68.6	50
28	RL28-M25-CSF90	LPA66-23-3/4-CSF90	M25X1.5	15.0	57.8	37.0	20.0	37.0	78.7	20
34	RL34-M32-CSF90	LPA66-29-1-CSF90	M32X1.5	15.0	67.8	43.5	25.5	47.0	92.9	20
42	RL42-M40-CSF90	LPA66-36-1-1/4-CSF90	M40X1.5	16.0	85.5	53.0	32.0	53.0	114.0	10
54	RL54-M50-CSF90	LPA66-48-1-1/2-CSF90	M50X1.5	16.0	98.0	66.0	42.5	63.0	131.5	5

PG 螺纹

适配软管尺寸 Fits to Conduit size	型号 Part no.	铁路专属型号① Special no.	螺纹 A Thread	B	C	D	E	F	G	包装(个) Packing
13	RL13-PG9-CSF90	LPA66-10-PG9-CSF90	PG9	12.0	41.1	20.0	10.5	24.0	60.8	50
16	RL16-PG11-CSF90	LPA66-12-PG11-CSF90	PG11	12.0	41.9	22.0	11.0	27.0	64.0	50
21	RL21-PG13-CSF90	LPA66-17-PG13-CSF90	PG13.5	14.0	48.1	28.5	14.5	32.0	68.6	50
21	RL21-PG16-CSF90	LPA66-17-PG16-CSF90	PG16	14.0	48.1	28.5	17.5	34.0	69.6	50
28	RL28-PG21-CSF90	LPA66-23-PG21-CSF90	PG21	14.0	56.8	37.0	20.5	39.0	79.7	20
34	RL34-PG29-CSF90	LPA66-29-PG29-CSF90	PG29	14.0	66.8	43.5	29.0	49.0	93.9	20
42	RL42-PG36-CSF90	LPA66-36-PG36-CSF90	PG36	16.0	85.5	53.0	38.0	59.0	117.0	10
54	RL54-PG48-CSF90	-	PG48	16.0	98.0	66.0	49.0	70.0	132.0	5

备注：铁路专属型号①为铁道客车，其他客车车辆，动车组及特种车辆专属型号。

Note: railway special model number is for railway passenger cars, other passenger vehicles, motor trains unit and special vehicle exclusive models

RL 金属内螺纹 90 度弯接头

RL 90° Elbow fitting with metal internal thread

材质：尼龙 66，黄铜镀镍螺纹

Material: Polyamide 66, Nickel plated brass thread

颜色：黑色 / 灰色

Colour: Black(BL) / Grey(GR)

温度：-45°C~+120°C，短时间 150°C

Temperature range: -45°C ~ +120°C, short-term to 150°C

防护等级：IP66, IP68(与软管及 RLS 密封垫配合使用)

Protection Degree: IP66, IP68(For use with conduits & RLS seal)

特性：自熄灭性好，不含卤素，磷，镉，同时具有极好的抗冲击强度

Properties: Self-extinguishing, free of halogen, phosphor and cadmium, with excellent impact strength.



CE  UL测试 EN45545

已通过铁道客车 67 号文件测试

UNEF 螺纹

适配软管尺寸 Fits to Conduit size	型号 Part no.	铁路专属型号① Special no.	螺纹 A Thread	B	C	D	E	F	G	包装(个) Packing
13	RL13-U063-CSF90	-	5/8" -24	14.0	43.1	20.0	10.7	24.0	60.8	50
16	RL16-U063-CSF90	-	5/8" -24	14.0	43.9	22.0	11.0	27.0	64.0	50
16	RL16-U075-CSF90	-	3/4" -20	14.0	43.9	22.0	11.0	27.0	64.0	50
21	RL21-U075-CSF90	-	3/4" -20	15.0	49.1	28.5	15.0	32.0	68.6	50
21	RL21-U081-CSF90	-	3/16" -20	15.0	49.1	28.5	15.0	32.0	68.6	50
28	RL28-U094-CSF90	-	15/16" -20	15.0	57.8	37.0	20.0	37.0	78.7	20
28	RL28-U100-CSF90	-	1" -20	15.0	57.8	37.0	20.0	37.0	78.7	20
34	RL34-U113-CSF90	-	1 1/8" -18	15.0	67.8	43.5	25.5	47.0	92.9	20
34	RL34-U119-CSF90	-	1 3/16" -18	15.0	67.8	43.5	25.5	47.0	92.9	20
34	RL34-U125-CSF90	-	1 1/4" -18	15.0	67.8	43.5	25.5	47.0	92.9	20
34	RL34-U131-CSF90	-	1 5/16" -18	15.0	67.8	43.5	25.5	47.0	92.9	20
34	RL34-U138-CSF90	-	1 3/8" -18	15.0	67.8	43.5	25.5	47.0	92.9	20
42	RL42-U144-CSF90	-	1 7/16" -18	16.0	85.5	53.0	32.0	53.0	114.0	10
42	RL42-U175-CSF90	-	1 3/4" -18	16.0	85.5	53.0	32.0	53.0	114.0	10
54	RL54-U200-CSF90	-	2" -18	16.0	98.0	66.0	42.5	63.0	131.5	5

备注：铁路专属型号①为铁道客车，其他客车车辆，动车组及特种车辆专属型号。

Note: railway special model number is for railway passenger cars, other passenger vehicles, motor trains unit and special vehicle exclusive models