

RL/X 金属外螺纹可旋转直接头

RL/X Straight fitting, swivel, with metal external thread



材质：尼龙 66，黄铜镀镍螺纹

Material: Polyamide 66, Nickel plated brass thread

颜色：黑色 / 灰色

Colour: Black(BL) / Grey(GR)

温度：-45°C~+120°C，短时间 150°C

Temperature range: -45°C ~ +120°C, short-term to 150°C

防护等级：IP66, IP68(与软管及 RLS 密封垫配合使用)

Protection Degree: IP66, IP68(For use with conduits & RLS seal)

特性：不含卤素和镉，极高的抗冲击强度，高强度的螺纹和系统连接，适用于偶然的旋转

Properties: Free of halogen and cadmium, very high impact resistance, high thread and system connection strength, suitable for occasional rotation.



CE UL测试 EN45545

M 螺纹

适配软管尺寸 Fits to Conduit size	型号 Part no.	螺纹 A Thread	B	C	D	E	F	包装 (个) Packing
16	RL16-M16-SA/X	M16X1.5	11.5	58.9	22.0	11.6	24.0	50
16	RL16-M20-SA/X	M20X1.5	14.0	61.4	22.0	11.6	24.0	50
21	RL21-M20-SA/X	M20X1.5	14.0	64.0	28.0	15.0	28.0	50
21	RL21-M25-SA/X	M25X1.5	16.0	67.0	28.0	15.0	30.0	50
28	RL28-M25-SA/X	M25X1.5	16.0	67.1	36.4	20.3	36.0	50
28	RL28-M32-SA/X	M32X1.5	16.0	67.1	36.4	20.3	40.0	50
34	RL34-M32-SA/X	M32X1.5	16.0	70.0	43.0	26.5	42.0	30
34	RL34-M40-SA/X	M40X1.5	16.0	70.0	43.0	26.5	50.0	30
42	RL42-M40-SA/X	M40X1.5	16.0	75.8	52.5	31.3	50.0	30
42	RL42-M50-SA/X	M50X1.5	16.0	75.8	52.5	31.3	60.0	30
54	RL54-M50-SA/X	M50X1.5	16.0	81.2	66.0	40.5	60.0	10
54	RL54-M63-SA/X	M63X1.5	16.0	81.2	66.0	40.5	70.0	10

PG 螺纹

适配软管尺寸 Fits to Conduit size	型号 Part no.	螺纹 A Thread	B	C	D	E	F	包装 (个) Packing
13	RL13-PG9-SA/X	PG9	12.0	53.2	19.5	11.6	24.0	50
16	RL16-PG11-SA/X	PG11	12.0	59.4	22.0	11.6	24.0	50
21	RL21-PG13-SA/X	PG13	13.0	64.0	28.0	15.0	28.0	50
21	RL21-PG16-SA/X	PG16	13.0	64.0	28.0	15.0	28.0	50
28	RL28-PG21-SA/X	PG21	14.0	65.1	36.4	20.3	36.0	50
34	RL34-PG29-SA/X	PG29	14.0	68.0	43.0	26.5	42.0	30
42	RL42-PG36-SA/X	PG36	17.0	76.8	52.5	31.3	52.0	30
54	RL54-PG48-SA/X	PG48	17.0	82.2	66.0	40.5	70.0	10