

31/32

RL/X 金属内螺纹可旋转 90 度接头

RL/X 90° Elbow fitting, swivel, with metal internal thread



材质：尼龙 66，阳极化铝螺纹

Material: Polyamide 66, anodized aluminium thread

颜色：黑色 / 灰色

Colour: Black(BL) /Grey(GR)

温度：-45°C~+120°C，短时间 150°C

Temperature range: -45°C ~ +120°C, short-term to 150°C

防护等级：IP66, IP68(与软管及 RLS 密封垫配合使用)

Protection Degree: IP66, IP68(For use with conduits & RLS seal)

特性：不含卤素和镉，极高的抗冲击强度，高强度的螺纹和系统连接，适用于偶然的旋转

Properties: Free of halogen and cadmium, very high impact resistance, high thread and system connection strength, suitable for occasional rotation.



CE UL测试 EN45545

UNEF 螺纹

适配软管尺寸 Fits to Conduit size	型号 Part no.	螺纹 A Thread	B	C	D	E	F	G	包装(个) Packing
13	RL13-U063-CSF90/X	5/8"-24UNEF	9.0	44.7	19.5	11.5	22.0	63.0	50
16	RL16-U063-CSF90/X	5/8"-24UNEF	9.0	46.8	22.0	11.6	23.0	65.3	50
16	RL16-U075-CSF90/X	3/4"-20UNEF	9.5	52.3	22.0	11.6	23.0	65.3	50
21	RL21-U075-CSF90/X	3/4"-20UNEF	9.5	52.3	28.0	15.0	28.0	70.0	50
21	RL21-U081-CSF90/X	13/16"-20UNEF	9.5	60.5	28.0	15.0	28.0	70.0	50
28	RL28-U094-CSF90/X	15/16"-20UNEF	9.5	60.5	36.5	20.3	35.0	80.0	20
28	RL28-U100-CSF90/X	1"-20UNEF	9.5	60.5	36.5	20.3	35.0	80.0	20
34	RL34-U113-CSF90/X	1 1/8"-18UNEF	9.5	77.5	43.0	26.5	41.0	100.0	20
34	RL34-U119-CSF90/X	1 3/16"-18UNEF	9.5	77.5	43.0	26.5	41.0	100.0	20
34	RL34-U125-CSF90/X	1 1/4"-18UNEF	9.5	77.5	43.0	26.5	41.0	100.0	20
34	RL34-U131-CSF90/X	1 5/16"-18UNEF	9.5	77.5	43.0	26.5	41.0	100.0	20
34	RL34-U138-CSF90/X	1 3/8"-18UNEF	9.0	77.0	43.0	26.5	41.0	100.0	20
42	RL42-U144-CSF90/X	1 7/16"-18UNEF	9.5	88.8	53.0	31.3	48.0	118.0	10
42	RL42-U175-CSF90/X	3/4"-18UNEF	11.5	90.8	53.0	31.3	48.0	118.0	10
54	RL54-U200-CSF90/X	2"-18UNEF	12.0	104.5	66.0	40.5	60.0	133.0	5